



**THE DOW CHEMICAL COMPANY
SALES SPECIFICATION**

Date Printed: 2022-08-23

Effective Date: 2019-02-28

Supersedes Date: 2018-11-29

Name: DOWSIL™ 3903 Liquid Satin Blend

Specification Number: 000000484899

Shelf Life

Container Type	Conditions of Handling	Conditions of Storage	Shelf Life	Deterioration Characteristics
All Approved Packaging			720 Days	

Final Testing Requirements

Test and Test Condition	Limit	Unit	Method	Note
Appearance, clear to translucent, colorless to, light amber, no significant particulate	Pass		CTM0176	
Viscosity, Steady Shear	1000 — 8000	cP	CTM1094	
Non Volatile Content, 2g/150C/3h/Al Cup, forced draft	7.0 — 7.5	%	CTM0208	
JSCI & JCIC - Description	Pass		CTM1238	
Test Frequency:	Warranted property once per year			
Infrared Identification	Pass		CTM0079	
Test Frequency:	Warranted property once per year			
Heavy Metal	20 Max	ppm	CTM1238	
Test Frequency:	Warranted property once per year			
Arsenic	2 Max	ppm	CTM1238	
Test Frequency:	Warranted property once per year			

**THE DOW CHEMICAL COMPANY
SALES SPECIFICATION**

Name: DOWSIL™ 3903 Liquid Satin Blend
Specification Number: 000000484899
Effective Date: 2019-02-28

Final Testing Requirements

Test and Test Condition	Limit	Unit	Method	Note
pH, Neutral	Pass		CTM0834	
Test Frequency:	Warranted property once per year			

External Notes

- The following properties are warranted to meet the indicated limits, for Japan JSQI/JSCI requirements.

Test Item -----	Limits -----
Description	Pass
Clear to translucent, colorless to light amber, no significant particulate, slight characteristic odor	
Infrared Identification	Pass
Heavy Metals	<= 20 ppm
Arsenic	<= 2 ppm
Neutral by pH test paper	Pass

READ PRECAUTIONARY INFORMATION AND MATERIAL SAFETY SHEETS. THIS PRODUCT IS SHIPPED IN COMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS REGARDING CLASSIFICATION, PACKAGING, SHIPPING AND LABELING.